

A New Gold Standard in Infusion Management

BodyGuard T34

Ambulatory Syringe Driver

The BodyGuard T34 Syringe driver is the new standard in ambulatory Syringe drivers. Offering a comprehensive range of features designed to maximize safe, economic and simple administration of medication via multiple program options.

BodyGuard is light, compact & robust ensuring it can be used in a wide variety of treatment settings including hospital in- and out-patient & homecare.

BodyGuard constitutes a major advance in technology incorporating active & passive safety features configurable to local practice and protocols and lockable to prevent use or change by unauthorized personnel.

These features include security access codes, free - flow protection (optional), downloadable patient and event history and automatic detection of a wide range of syringes from 3 to 50 ml. BodyGuard T34 software can be adjusted to local users needs including choice of language for information display.

Manufactured by: Caesarea Medical Electronics Limited
Address: Staufenburgstr. 23, Lichtenstein
POB 1248, Lichtenstein 72805, Germany.

©2004 by Caesarea Medical Electronics Ltd. All rights reserved.
BodyGuard is a registered trademark of C.M.E. Ltd.

www.cme-infusion.com

Free toll Tel no.: 1-800-323-575-00
FDA Approved 510K NO K31749



- **Lightweight & Compact** – BodyGuard T34 is the most compact & lightest pump in its class.
- **Optional pole-mounting in a dual channel charger** enables treatments where multiple drug delivery is indicated.
- **Comprehensive range of pump accessories** including shoulder carry bag, lockable syringe cover and charger.
- **3 levels of Access Security Codes**, ensures only authorised personnel can use the device and only senior personnel can set up the devices parameters.
- **Downloadable 24 Hour Patient History** (including charts) & **1000 Event Log** for full accountability & technical data.



BodyGuard T34 Ambulatory Syringe Driver

Speed Range	from 0.1 to 1000 ml/h (from 0.1 to 100 ml/h in 0.1ml/h increments From 100 to 1000 ml/h in 1ml/h increments)
Time Range	from 10 Minutes to 100 Hours
Dimensions	165 x 23 x 40mm (6.5 x 0.9 x 1.8 inches)
Weight	180 grams including batteries
Battery Type	Alkaline 9v Batteries
Battery Life	100 full Syringes
Controls	Graphic Display 122 x 32 pixels with back light (8 keys) & dual color operation LED
Syringe range	3ml to 50 ml syringe (any brand)
Languages	Selectable- English, Italian, Spanish

Alarms

Occlusion	Downstream (between pump & patient)
End Program	Program Completed
Near End	Program nearing completion
End Travel	Empty Syringe
Low Battery	Battery charge is lower than 7v
End Battery	Battery Depleted
Check program	Wrong Setting - (protocol requested is outside of safe limits set by senior personnel under level three access code)
High Pressure	the pressure in the line has exceeded the pre-set limit

Features

- Automatic detection of the syringe size and brand
- Programs : Continuous, Intermittent, PCA (Bolus)
- Serial Port (RS232) connection
- DC connection to a mains transformer
- 1000 Protocols to be selected.
- Ambulatory or Pole mounted configuration.